

DMInteract®

From Visualization to Collaboration



DMInteract DM2.5MM-OD

P2.5mm High Resolution SMD
Technology Outdoor Dot LED
Video Wall Displays



BEST IN CLASS

DMINTERACT DM2.5MM-OD

**P2.5mm High Resolution SMD Technology
Outdoor Dot LED Video Wall Displays**

**Available Sizes:
100", 150", 180" And 200"**

PRODUCT OVERVIEW

The DMInteract P2.5mm High Resolution SMD Technology Outdoor Dot LED Video Wall Display offers exceptional clarity with a 2.5mm pixel pitch and a high brightness level of $\geq 5000\text{cd/m}^2$, ensuring vibrant visuals even in bright outdoor environments. Its wide viewing angle of 140-160 degrees provides excellent visibility from various perspectives, while the robust yet lightweight die-casting aluminum cabinet, weighing only 8kg per piece, facilitates easy installation. With a refresh rate of 3840Hz, the display ensures smooth video playback. It is energy-efficient, with an average power consumption of $260\text{-}450\text{W/m}^2$, and designed to last with a lifespan of $\geq 100,000$ hours. Operating reliably in extreme temperatures from -30°C to 65°C and humidity levels from 10% to 90%, this display is perfect for diverse outdoor climates. Featuring RGB pixel configuration and SMD1415 LED lamps, it delivers accurate color reproduction, and its modular design allows for easy setup and scalability.



Specifications of the DMInteract DM2.5MM-OD Outdoor Dot LED Solution:

Brand Name:	DMInteract
Model Number:	DM2.5MM-OD
Suitable For:	Outdoor
Pixel Pitch:	P2.5mm
Module Size:	320x160mm
Module Resolution:	128x64 Pixels
Pixel Configuration:	RGB
LED Lamp:	SMD1415
Driving Method:	1/16scan
Pixel Density:	160000 Pixels/SQM
Refresh Rate:	3840Hz
Viewing Angle:	140-160 Degrees
Brightness:	≥5000cd/m²
Cabinet Size:	640x640mm

Specifications of the DMInteract DM2.5MM-OD Outdoor Dot LED Solution:

Cabinet Resolution:	256x256 Pixels
Cabinet Material:	Die-Casting Aluminum
Average Consumption:	260-450W/m²
Max. Consumption:	950 W/m²
Input Voltage:	AC220V-240V/50-60Hz
Operating Humidity:	10% ~ 90%
Operating Temperature:	-30°C~65°C
Life Span:	≥100,000 Hours
Cabinet Weight:	8kg/pc

Available Sizes Of The DMInteract DM2.5MM-IN Outdoor Dot LED Solution:

DMInteract 100" Outdoor P2.5mm Dot LED Display

Screen Size: 1.92(W) x 1.28(H)m = 2.46sqm

Diagonal Size: Around 100"

Refresh Rate: 3840Hz

Cabinet Quantity: 3 x 2 = 6 Units

DMInteract 150" Outdoor P2.5mm Dot LED Display

Screen Size: 3.2(W) x 1.92(H)m = 6.144sqm

Diagonal Size: Around 150"

Refresh Rate: 3840Hz

Cabinet Quantity: 5 x 3 = 15 Units

DMInteract 180" Outdoor P2.5mm Dot LED Display

Screen Size: 3.84(W) x 1.92(H)m = 7.37sqm

Diagonal Size: Around 180"

Refresh Rate: 3840Hz

Cabinet Quantity: 6 x 3 = 18 Units

DMInteract 200" Outdoor P2.5mm Dot LED Display

Screen Size: 4.48(W) x 2.56(H)m = 11.5sqm

Diagonal Size: Around 200"

Refresh Rate: 3840Hz

Cabinet Quantity: 7 x 4 = 28 Units



SPECIAL OFFER

ORDER NOW



 **DEALER ADDRESS:**

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates

 **CANADA OFFICE:**

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9

 **CONTACT NUMBER:**

+971-4-3360300 - (Dubai Office)

437-880-7712 - (Mississauga Office)

 **EMAIL ADDRESS:**

info@dminteract.com